

Rocky CM8



Rocky CM8, based on the Intel Core 2 Duo processor is built for high performance.

It has low power consumption, high connectivity and no fan for quiet and reliable operation.

The display is a 17" WXGA LCD (1400*900) and the case is made out of magnesium.

Rocky CM8

Specifications*



Intel Pentium Core 2 Duo 1.6 Ghz, 4 MB level-II cache

RAM 512 MB - 4 GB DDRII 667MHz

Integrated 32-bit 3D/2D gfx core with max 128 MB shared RAM

17" WXGA (1400*900) TFT LCD, ~200 cd/m²

Built in AC97 compliant 16-bit audio controller with stereo speakers

89-key keyboard, standard keycap or optional backlit type

PS/2 compatible touchpad

Removable 11,1 V 6600 mAH Lithium-Ion primary battery

Built in vehicle adapter (12-32V DC)

Magnesium case

Size: 410 mm x 313.5 mm x 68.2 mm. (WxDxH)

Weight approximately 6.5 Kg (depends on configuration)

Standard ports:

Speaker, Microphone, Line-In, 3 x USB 2.0, 1 x IEEE1394, Docking

PS/2 (Mouse/Kbd), DVI, RGB, DC, Printer, 2 x RS232 (DB9)

1 x type I or type II exchangeable PCMCIA slot

1 x Express Card

Optional ports:

Fax/Modem, Gigabit-LAN, 100 base FX fibre (LC)

4 x Military connectors, 2 x Serial COM 3/4 (DB9)

Options*

Bay 1: Removable 2.5" SATA HDD, 120GB max

Bay 2: Removable 3.5" FDD, HDD, CD/RW, DVD, DVD/RW, or secondary battery

2 x PCMCIA type I or type II (trades off Express Card)

4 x Mil Connector upgrade (rear of computer) for RS232, Video etc (MIL-DTL-38999)

Mil connector for DC

DIMM card: 512/1024/2048 MB (max 4 GB)

Secondary battery 6600 mAH Lithium Ion

NVIDIA MXMII 256MB Graphics

WLAN (IEEE802.11b,g)

GPRS/EDGE

GPS

Bluetooth v2.0

Modem card

Gigabit LAN

Internal 100 base FX fibre (LC)

COM 3/4 (RS232/RS422/RS485)

89-keys backlit keyboard

Touch screen (resistive)

DockUnder-Office

DockUnder-Vehicle



LOGiN

LogIn Crete AB
Box 22079, 250 22 Helsingborg
Tel +46 42 250000, Fax +46 42 250025
email info@login.se
www.login.se

* Login reserves the right to update the information at any time without notice.